

# Currency Exchange Rates (POST)

## Overview

This POST API can be used to save the Currency Exchange Rates received from the ERP to GEP Quantum

URL Format: <https://<instance>.gep.com/leo-centraldata-exchangerateservice/api/v1/ExchangeRateMaster/Multiple>

## Request

```
[
  {
    "clientCode": "code-01",
    "sourceSystem": "API",
    "isActive": true,
    "targetCurrency": "EUR",
    "reverseExchangeRate": 0.0312,
    "isDefault": false,
    "effectiveDate": "2023-08-02T08:08:30.091Z",
    "fromCurrency": "USD",
    "exchangeRate": 50.12
  },
  {
    "clientCode": "code-02",
    "sourceSystem": "API",
    "isActive": true,
    "targetCurrency": "USD",
    "reverseExchangeRate": 0.0312,
    "isDefault": false,
    "effectiveDate": "2023-08-02T08:08:30.091Z",
    "fromCurrency": "EUR",
    "exchangeRate": 50.12
  }
]
```

## Response

```
{
  "returnValue": {
    "totalCount": 1,
    "successCount": 1,
    "errorCount": 0,
    "failedRequests": [
    ],
    "successResult": {
      "successIdentifiers": [
        {
        }
      ]
    },
    "id": 200,
    "status": "Success",
    "errors": null,
    "_id": null,
    "_ids": [
      "1"
    ]
  },
  "isSuccess": true,
  "errors": null,
  "exception": null,
  "errorMessage": null,
  "errorCode": null,
  "correlationId": null
}
```

## Data Elements

PROPERTY	REQUIRED	DATA TYPE	DESCRIPTION
_id	Yes	string	<ul style="list-style-type: none"> <li>Mandatory for delete, update operation.</li> <li>_id of the Exchange Rate</li> </ul>
clientCode	No	string	<ul style="list-style-type: none"> <li>Non-Mandatory field</li> <li>Unique field</li> </ul>
fromCurrency	Yes	String (10)	<ul style="list-style-type: none"> <li>Mandatory field</li> <li>Max length is 10.</li> <li>Validated from Currency against code.</li> </ul>
targetCurrency	Yes	String (10)	<ul style="list-style-type: none"> <li>Mandatory field</li> <li>Max length is 10.</li> <li>Validated from Currency against code.</li> </ul>
reverseExchangeRate	No	Decimal	<ul style="list-style-type: none"> <li>Non-Mandatory field</li> <li>Upto 9 integers before decimal and upto 15 integers after decimal</li> </ul>
exchangeRate	Yes	Decimal	<ul style="list-style-type: none"> <li>Non-Mandatory field</li> <li>Upto 9 integers before decimal and upto 15 integers after decimal</li> <li>If from &amp; to currency are set as same, then the conversion rate will default to 1 irrespective of the exchange rate entered.</li> <li>Default value - 0</li> </ul>
effectiveDate	Yes	string(date-time)	<ul style="list-style-type: none"> <li>Mandatory field</li> <li>The allowed date format is DD/MM/YYYY</li> <li>Please enter date only in this format</li> </ul>
sourceSystem	Yes	string	<ul style="list-style-type: none"> <li>Default value is "API."</li> </ul>

isActive	No	bool	<ul style="list-style-type: none"> <li>• Default value is TRUE.</li> </ul>
isDefault	No	bool	<ul style="list-style-type: none"> <li>• Default value is FALSE.</li> <li>• Only one true value is allowed.</li> </ul>
lobCode	Yes - when IsLobRequired flag is enabled.	string	<ul style="list-style-type: none"> <li>• Validated from Organization Structure.</li> <li>• Mandatory when IsLobRequiredflag is enabled.</li> <li>• When this flag is disabled lobCode will be <b>ALL</b></li> </ul>

## Validation

Property	Scenario	Error Message
clientCode	If record is already present for given client code.	Record Already Exists for given Client Code
sourceSystem	<ol style="list-style-type: none"> <li>1. Incorrect source system value.</li> <li>2. Null/Empty value</li> </ol>	<ol style="list-style-type: none"> <li>1. Invalid Source system value.</li> <li>2. Value cannot be null/empty.</li> </ol>
targetCurrency	Incorrect currency code.	Invalid target currency.
reverseExchangeRate	Value outside the allowed range.	Input string not a valid decimal.
effectiveDate	Incorrect format of date	Cannot convert string to Date Time.
fromCurrency	Incorrect currency code.	Invalid base currency.
exchangeRate	Value outside the allowed range.	Input string not a valid decimal.