

# GetGeneralLedgerDetails (GET)

## Overview

This GET API can be used to retrieve General Ledger details in SMART by GEP to post them into ERP.

URL Format: <https://<Instance>/SmartInterfaceAPI/api/GeneralLedger/All>

## Request

<https://<Instance>/SmartInterfaceAPI/api/GeneralLedger/All>

## Response

```
{
  "data": [
    {
      "name": "String",
      "code": "String",
      "coaCode": "String",
      "description": "String",
      "isDeleted": true,
      "isActive": true,
      "categories": [
        {
          "pasCode": 0,
          "isDefault": true,
          "clientPasCode": "String",
          "isDeleted": true
        }
      ]
    }
  ]
}
```

```

    ],
    "statusCode": "String",
    "errorDetails": [
      {
        "key": "string",
        "errors": [
          {
            "errorCode": "string",
            "errorDescription": "string"
          }
        ]
      }
    ]
  },
  "successDetails": [
    {
      "key": "String"
    }
  ]
]
}

```

## Data Elements

Get General Ledger				
Property	Required?	Data type	Description	Validations/Exceptions
<a href="#">Data</a>		List of GeneralLedger object		
StatusCode		String		
<a href="#">ErrorDetails</a>		List of ErrorModel object		
<a href="#">SuccessDetails</a>		List of SuccessModel object		

Data				
Property	Required?	Data type	Description	Validations/Exceptions
Name		String	Name of entity	
Code		String	Code of entity	
COACode		String	COACode of entity	

Description		String	Description of entity	
IsDeleted		Boolean	A flag used to denote if entity is soft deleted or not	
IsActive		Boolean	A flag used to denote if entity is active or not	
<a href="#">Categories</a>		List of PAS object	Check data type PAS for details.	

Categories				
Property	Required?	Data type	Description	Validations/Exceptions
PasCode		Long	Pas Code of entity	
IsDefault		Boolean	Status of the entity if this is default or not	
ClientPasCode		String	Client Pas Code of entity	
IsDeleted		Boolean	Status of the entity on whether it should be visible on the application or not	

ErrorDetails				
Property	Required?	Data type	Description	Validations/Exceptions
Key		String		
<a href="#">Errors</a>		List of Error object		

Errors				
Property	Required?	Data type	Description	Validations/Exceptions
ErrorCode		String		
ErrorDescription		String		

SuccessDetails				
Property	Required?	Data type	Description	Validations/Exceptions
Key		String		

## Examples

### Success Scenario - Request

<https://<Instance>/SmartInterfaceAPI/api/GeneralLedger/All>

## Success Scenario – Response

```
{
  "data": [
    {
      "name": "434405 Other Business Services",
      "code": "434405",
      "coaCode": "1000",
      "description": "434405 Other Business Services",
      "isDeleted": true,
      "isActive": false,
      "categories": [
        {
          "pasCode": 14450250001993,
          "isDefault": true,
          "clientPasCode": ""
        }
      ]
    }
  ],
  "statusCode": "200",
  "errorDetails": [],
  "successDetails": []
}
```